



OPTIMISED PAINT SYSTEM

Flexible Paint Cups & Accessories Process Chart

Two piece paint cup system for the preparation & application of both solvent and water based paints

Before Spraying



Wear protective clothing

Flexible Paint Cups

- 125 micron filter 300ml
- 190 micron filter 300ml
- 125 micron filter 600ml
- 190 micron filter 600ml

Code

- PSC301**
- PSC306**
- PSC601**
- PSC606**

Accessories

- Stoppers
- Rigid Clear Cups 650ml
- printed
- blank

PSS001

Adaptors

- Adaptor Type A
- Adaptor Type B
- Adaptor Type C
- Adaptor Type D
- Adaptor Type E
- Adaptor Type F
- Adaptor Type G
- Adaptor Type H
- Adaptor Type L
- Adaptor Type Q (SATA QCC Adaptor - use with Type E)
- Adaptor Type R
- Adaptor Type S
- Adaptor Type T

- PSA00A**
- PSA00B**
- PSA00C**
- PSA00D**
- PSA00E**
- PSA00F**
- PSA00G**
- PSA00H**
- PSA00L**
- PSA00Q**
- PSA00R**
- PSA00S**
- PSA00T**

How to Use



Step 1:
Degrease the surface before use



Step 2:
Pour paint into the Flexible Paint Cup



Step 3:
IMPORTANT!
Do not overfill the Flexible Paint Cup - ensures correct collapse of cup in use



Step 4:
Twist on the lid



Step 5:
No leakage thanks to screw-fit lid and no valve



Step 6:
Twist on correct adaptor and gun



Step 7:
The Flexible Paint Cup will gradually collapse as the paint is used



Can spray in all directions, including inverted



Step 8:
Flexible Paint Cups can be easily re-filled if necessary



Step 9:
Used Flexible Paint Cup collapses down further to minimise waste space used



Store 1:
If the paint isn't finished, apply a Stopper to keep the paint fresh



Store 2:
Store upside down to prevent the filter from drying out which enables it to be re-used

Note



Write on the base when kept upside down or use labels



Search on YouTube for **Farécla Optimised Paint System**