



GENERAL INFORMATION

1-951 Silicone Remover Standard Silicon Remover.

MIXING RATIO



-

GUN SET UP



	NOZZLE (MM)	AIR PRESSURE (BAR / PSI)
HVLP	-	-
HE	-	-

APPLICATION



-

FLASH OFF AND DRY TIMES



AIR DRY 20°C / 68°F		FORCED DRY 60°C / 140°F	
Flash off	-	Flash off	-
Dust free	-	Dust free	-
Dry to handle	-	Dry to handle	-
Dry to tape	-	Dry to tape	-
Dry to sand	-	Dry to sand	-
Dry to polish	-	Dry to polish	-



SUBSTRATES



Bare Steel, old and new paint systems.

POT LIFE AT 20°C / 68°F



-

COMPONENTS



-

ADDITIVES



-

SURFACE PREPARATION



-



NEXT LAYER



-

PHYSICAL DATA

EU REGULATIONS	
VOC Code	2004/42/IB(a)(850)759
Product sub category (according directive 2004/42/EC) and max VOC content (ISO 11890-1/2) of the ready to use product.	IIB/a. Preparatory and cleaning - Preparatory. EU limit values: 850 g/l. (2007) This product contains a maximum of 759 g/l VOC.
Chemical Base	Mix of organic solvents
Viscosity (RT5)	-
Specific Gravity (kg/l)	0.76
Flash Point Closed Cup	9°C / 48.2°F
Volume % Solids	-
Physical Properties	-
Economy	-
Gloss	-
Colour	-

PROTECTION

Use suitable respiratory protection (*fresh air supply respirator is strongly recommended*).



For more detailed information please visit the following link for the Safety Data Sheet:

https://sds.de-beer.com/en/debeer/choose_localization

CLEAN UP



-

STORAGE/SHELF LIFE

Minimum 2 years; (Under normal storage conditions 10°C - 30°C / 50°F - 90°F) (unopened container).



NOTES

-